

# BOND TAPE 01

## Single-sided Aluminum Foil Butyl Tape

### Product Description

This product is a self-adhesive waterproofing membrane meticulously manufactured using butyl rubber as the primary material through a series of processing techniques. It possesses excellent water and air impermeability, can be directly applied to clean substrates, and quickly forms a tight bond with the substrate, effectively preventing water tracking.



### Product Features

- Easy application, labor and time-saving.
- Excellent weather resistance, water impermeability, and air tightness.

### Product Information

#### Specification

1.2mm \* 10cm \* 5m

### Precautions

- Substrate must be clean, dry, and level.
- After application, use a roller to compact the tape, avoiding any gaps that could allow water tracking.
- Recommended application temperature is between 5° C and 45° C.

### Where To Use

Suitable for repair, waterproofing, and seepage prevention on materials such as concrete and color steel plates.

### Storage And Transportation

- During storage and transportation, products of different types and specifications should be stacked separately and not mixed. Avoid direct sunlight and rain, ensure adequate ventilation.
- Storage temperature should not exceed 45° C. Under normal transport and storage conditions, the shelf life is at least one year from the production date.

## Technical Data Based For Reference

Implemented standard: Q/SDKS 110-2024

NO.	Item	Index
1	Heat Resistance, 80°C	No flow, cracking, or deformation
2	Low-temperature Flexibility, -25°C	No cracks
3	Peel Strength	Color Steel Plate $\geq 0.4$
		Cement Mortar Board $\geq 0.4$