

CKS Wall Repair

Eco-Friendly Wall Repair Paint



Product Description

CKS Wall Repair is specially designed for DIY use. It comes with a built-in roller and is ready to apply straight from the container. The product offers strong coverage, effectively covering fine cracks and stains on walls, and provides powerful mold resistance, making it suitable for partial renovation of interior wall surfaces.

Packaging

500g

Product Features

- Strong hiding power
- Alkali & Scrub Resistance
- Fine Film & Sag-Resistant
- Efficient Large-Area Application

Where to Use

Suitable for covering various wall stains such as mold, yellowing, and graffiti.

Application Instructions

- Remove dust, loose paint and other loose materials from the damaged wall surface.
- This product comes with a built-in roller. After opening the lid, dip the roller directly into an appropriate amount of paint and apply evenly onto the area to be repaired.
- It is recommended to apply in thin, multiple coats, allowing each coat to dry completely before applying the next.

Precautions

- Remove all loose, hollow, peeling or powdery damaged areas, then patch to a smooth, even surface.
- After each coat is applied, allow it to dry thoroughly before proceeding with the next coat.
- If the applied surface is uneven, sand it smooth with sandpaper after fully dry.
- Before application, protect the floor to prevent drips and keep it clean.
- If not fully used, seal and store in a cool, dry place at 5° C–35° C.

Transportation And Storage

- This product is non-flammable and non-explosive, and can be transported as general cargo. During transport, protect from rain, direct sunlight, freezing, and package damage.
- Store in a dry, well-ventilated and cool place at a temperature between 5° C and 35° C.
- Shelf life: 12 months from production date under normal storage and transport conditions.